

DRYER-POLYMERIZER ROLLER SHUTTER KILN Model RS

TECHNICAL SHEET

USE

Dryer-Polymerizer Kiln to dry the screen after emulsion application or to polymerize the same after the application of hardeners.

RECOMMENDED PRODUCTS

Emulsions serie CERAGEL and hardener GELHARD



TECHNICAL FEATURES

- Painted steel structure
- External walls completely insulated
- Automatic opening and closing roller shutter made by insulated alluminum
- Maximum operating temperature 100°C
- Complete of internal rack with 10 shelves for positioning of any size of frames
- Thermostat with digital display
- Drying or polymerizing is made by hot air fans
- Several models or sizes are available on demand

<i>Code</i>	<i>Name</i>	<i>Model</i>	<i>Useful size of shelves mm.</i>	<i>Overall dimensions mm.</i>
AQSFOEP135100	Roller Shutter Kiln 10 shelves	RS 1351	1350x1000	mm. 1730x1230x2100 h.
AQSFOEP200120	Roller Shutter Kiln 10 shelves	RS 2012	2000x1200	mm. 2500x1430x2100 h.

Seedex s.r.l.

Via Falzarego 9/9A - 41049 Sassuolo (MO) Italy - Tel: +39 0536 905606 Fax: +39 0536 815690
Cap.Soc. € 50.000,00 i.v. - P.IVA e Cod.Fisc. 03347160362 - http:// www.seedex.it - e-mail: mail@seedex.it